



The XT- Series tire wash packages are designed for Track Out Control at job sites, mines, quarries and other high traffic locations. This is InterClean Equipment's standard duty tire wash package for medium to heavy applications offering one and two full tire revolution cleaning options. Includes galvanized steel tire wash platforms with integrated nozzles and side impact nozzles for wheel well and rocker panel washing.

- Two galvanized steel tire wash platforms with integrated nozzles
- Side impact nozzles for wheel well and rocker panel washing

**XT- 40:** Single tire revolution wash capable of processing 40 – 60 vehicles per hour.

**XT-80:** Two tire revolution wash capable of processing 60 – 120 vehicles per hour.

# XT-40 AND XT-80 TIRE WASH

Equipment	Specifications XT40	Specifications XT-80
Dimensions	XT-40: 15' L x 9' W x 6' H, ISO Container 20'	XT-80: 30' L x 9' W x 6' H ISO Container 20'
Acceptable Vehicle	8'-6" Wide	8'-6" Wide
Gross Weight (Approximately)	3500 lbs. Tire Wash ISO Container 4550 lbs.	7000 lbs. Tire Wash ISO Container 4550 lbs.
Sensor	Dual Photo Sensor	Dual Photo Sensor
Pump	2 - 20hp (15kw) Self-Priming Centrifugal 460V 60hz	4 - 20hp (15kw) Self-Priming Centrifugal 460V 60hz
Pump Manufacturer	Xylem	Xylem
Air Compressor	2 - 2hp 460V 60hz	4 - 2hp 460V 60hz
Water Volume	800 gpm	1600 gpm
Water Pressure	60 PSI	60 PSI
Main Power	460V 60hz 61A	460V 60hz 117A
Max Axle Weight	40,000 lbs	40,000 lbs
Capacity	Over 600 Trucks Per Day	Over 1200 Trucks Per Day
Side Spray Walls	Galvanized Steel	Galvanized Steel